



Connecting Strength

Imagen	Producto	Torque
	K2 Cross Clamp PNs: 4000135 & 4000145	12 ft-lb (16.3 Nm)
	T-Bolts PNs: 4000048 & 4000122	T-Bolts M10: 25.8 ft-lb (35.0 Nm)
	Climber Set PNs: 4006042-H & 4006043	M8 Bolt: 10.3 ft-lb (14.0 Nm)
	K2 Ground Lug PN: 4000006-H	M8 Bolt: 10.3 ft-lb (14.0 Nm) Terminal Bolt: 3-5 ft-lb (3.9-6.8 Nm)
	Yeti Clamp 2.0 PN: 4000050-B	12 ft-lb (16.3 Nm)
	Standing Seam Rail-less PN: 4000532	24 Steel 12.5 ft-lb (16.9 Nm) 13.3 ft-lb (18.0 Nm) 22 Steel 15 ft-lb (20.3 Nm) 16.6 ft-lb (22.6 Nm)
	Standing Seam PowerClamps PNs: 4000016 & 4000017	24 Steel 12.5 ft-lb (16.9 Nm) 13.3 ft-lb (18.0 Nm) 22 Steel 15 ft-lb (20.3 Nm) 16.6 ft-lb (22.6 Nm)
	CR Micro Inverter & OPT Mounting Kit PN: 4000629-H	M8 Hex Bolt: 10.3 ft-lb (14.0 Nm)
	MLPE Module Frame Mounting Kit PN: 4000083	10.3-18.5 ft-lb (14-25 Nm)
	ILSCO Lug PN: 4000960	Mounting Bolt: 6.2 ft-lb = 8.40 Nm Terminal Bolt: 3-5 ft-lb (3.9-6.8 Nm)

